

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Trade name	: CAMEL #EU11062F
UFI	: KRMY-201R-T00W-7A6K
Product code	: EU11062F
Type of product	: Perfumes, fragrances
Product group	: Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category	: Industrial use, Professional use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH  
Mittlerer Weg 35  
DE- 79424 Auggen  
Germany  
T 49-7631-931-8900  
[SDS@frenchcolor.com](mailto:SDS@frenchcolor.com) - [www.frenchcolor.com](http://www.frenchcolor.com)

#### 1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China: +400-120-0751; Mexico: +01-800-099-0731;  
Brazil: +0-800-591-6042; India: +000-800-100-4086

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4	H302
Serious eye damage/eye irritation, Category 2	H319
Skin sensitisation, Category 1	H317
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411
Full text of H- and EUH-statements: see section 16	

##### Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes serious eye irritation. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS09

Signal word (CLP)

: Warning

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H302 - Harmful if swallowed. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
Extra phrases	: For professional users only.

### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	40.9 – 81.79	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	4.2 – 8.45	Eye Irrit. 2, H319
Methyl ester of rosin (partially hydrogenated)	CAS-No.: 8050-15-5 EC-No.: 232-476-2	1.6 – 3.1	Aquatic Chronic 3, H412
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	1.3 – 2.5	Eye Irrit. 2, H319
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.6 – 1.2	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Heliotropine	CAS-No.: 120-57-0 EC-No.: 204-409-7 REACH-no: 01-2119983608-21	0.5 – 0.9	Skin Sens. 1B, H317

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetyl propionyl substance with national workplace exposure limit(s) (DE, SI, CH)	CAS-No.: 600-14-6 EC-No.: 209-984-8	0.4 – 0.8	Flam. Liq. 2, H225 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT RE 2, H373
1,2-Cyclopentanedione, 3-methyl-	CAS-No.: 765-70-8 EC-No.: 212-154-8	0.2 – 0.45	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317
Isobutyl acetate substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH)	CAS-No.: 110-19-0 EC-No.: 203-745-1 EC Index-No.: 607-026-00-7	0.1 – 0.2	Flam. Liq. 2, H225 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Obtain emergency medical attention. Rinse mouth. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
---------------------------	---

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store in a well-ventilated place. Keep cool.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight.

Storage temperature : 25 °C

Storage area : Store in a well-ventilated place. Store away from heat.

Special rules on packaging : Store in a closed container.

Packaging materials : Do not store in corrodable metal.

### 7.3. Specific end use(s)

No additional information available

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

acetyl propionyl (600-14-6)	
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	0.083 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	0.02 ppm
Chemical category	Skin notation, Skin sensitization
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	0.083 mg/m <sup>3</sup>
OEL TWA [ppm]	0.02 ppm
OEL STEL	0.083 mg/m <sup>3</sup>
OEL STEL [ppm]	0.02 ppm
OEL chemical category	Potential for cutaneous absorption
<b>Switzerland - Occupational Exposure Limits</b>	
MAK (OEL TWA) [1]	0.08 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	0.02 ppm
KZGW (OEL STEL)	0.16 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	0.04 ppm
OEL chemical category	Sensitizer, Skin notation
<b>Isobutyl acetate (110-19-0)</b>	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	241 mg/m <sup>3</sup> (Butyl acetates)
MAK (OEL TWA) [ppm]	50 ppm (Butyl acetates)
MAK (OEL STEL)	480 mg/m <sup>3</sup> (Butyl acetate)
MAK (OEL STEL) [ppm]	100 ppm (Butyl acetate)
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	238 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	712 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Bulgaria - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Croatia - Occupational Exposure Limits</b>	
GVI (OEL TWA) [1]	241 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	50 ppm

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Isobutyl acetate (110-19-0)</b>	
KGVI (OEL STEL)	723 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	150 ppm
<b>Cyprus - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Czech Republic - Occupational Exposure Limits</b>	
PEL (OEL TWA)	241 mg/m <sup>3</sup>
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA [1]	241 mg/m <sup>3</sup> (Butyl acetate, all isomers)
OEL TWA [2]	50 ppm (Butyl acetate, all isomers)
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Finland - Occupational Exposure Limits</b>	
HTP (OEL TWA) [1]	240 mg/m <sup>3</sup> (Butyl acetate)
HTP (OEL TWA) [2]	50 ppm (Butyl acetate)
HTP (OEL STEL)	725 mg/m <sup>3</sup> (Butyl acetate)
HTP (OEL STEL) [ppm]	150 ppm (Butyl acetate)
<b>France - Occupational Exposure Limits</b>	
VME (OEL TWA)	241 mg/m <sup>3</sup> (restrictive limit)
VME (OEL TWA) [ppm]	50 ppm (restrictive limit)
VLE (OEL C/STEL)	723 mg/m <sup>3</sup> (restrictive limit)
VLE (OEL C/STEL) [ppm]	150 ppm (restrictive limit)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
AGW (OEL TWA) [1]	300 mg/m <sup>3</sup> (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
AGW (OEL TWA) [2]	62 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Isobutyl acetate (110-19-0)</b>	
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	241 mg/m <sup>3</sup>
CK (OEL STEL)	723 mg/m <sup>3</sup>
OEL chemical category	Sensitizer
<b>Ireland - Occupational Exposure Limits</b>	
OEL TWA [1]	241 mg/m <sup>3</sup>
OEL TWA [2]	50 ppm
OEL STEL	723 mg/m <sup>3</sup> (calculated)
OEL STEL [ppm]	150 ppm (calculated)
<b>Italy - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (OEL TWA)	241 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	723 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	150 ppm
<b>Luxembourg - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Malta - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Netherlands - Occupational Exposure Limits</b>	
TGG-8u (OEL TWA)	241 mg/m <sup>3</sup>
TGG-8u (OEL TWA) [ppm]	50 ppm
TGG-15min (OEL STEL)	723 mg/m <sup>3</sup>
TGG-15min (OEL STEL) [ppm]	150 ppm
<b>Poland - Occupational Exposure Limits</b>	
NDS (OEL TWA)	240 mg/m <sup>3</sup>

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Isobutyl acetate (110-19-0)</b>	
NDSCh (OEL STEL)	720 mg/m <sup>3</sup>
<b>Portugal - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup> (indicative limit value)
OEL TWA [ppm]	50 ppm (indicative limit value)
OEL STEL	723 mg/m <sup>3</sup> (indicative limit value)
OEL STEL [ppm]	150 ppm (indicative limit value)
<b>Romania - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Slovakia - Occupational Exposure Limits</b>	
NPHV (OEL TWA) [1]	480 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	100 ppm
NPHV (OEL C)	700 mg/m <sup>3</sup>
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	241 mg/m <sup>3</sup>
OEL TWA [ppm]	50 ppm
OEL STEL	723 mg/m <sup>3</sup>
OEL STEL [ppm]	150 ppm
<b>Spain - Occupational Exposure Limits</b>	
VLA-ED (OEL TWA) [1]	241 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	50 ppm
VLA-EC (OEL STEL)	723 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	150 ppm
<b>Sweden - Occupational Exposure Limits</b>	
NGV (OEL TWA)	241 mg/m <sup>3</sup> (Butyl acetates)
NGV (OEL TWA) [ppm]	50 ppm (Butyl acetates)
KTV (OEL STEL)	723 mg/m <sup>3</sup> (Butyl acetates)
KTV (OEL STEL) [ppm]	150 ppm (Butyl acetates)
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	724 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	150 ppm
WEL STEL (OEL STEL)	903 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	187 ppm
<b>Norway - Occupational Exposure Limits</b>	
Grenseverdi (OEL TWA) [1]	241 mg/m <sup>3</sup>
Grenseverdi (OEL TWA) [2]	50 ppm
Korttidsverdi (OEL STEL)	723 mg/m <sup>3</sup> (value from the regulation)



# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isobutyl acetate (110-19-0)	
Korttidsverdi (OEL STEL) [ppm]	150 ppm (value from the regulation)
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA) [1]	240 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	720 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	150 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	50 ppm (Butyl acetates, all isomers)
ACGIH OEL STEL [ppm]	150 ppm (Butyl acetates, all isomers)

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Chemical goggles or safety glasses. Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves. Wear protective gloves.

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

#### 8.2.2.4. Thermal hazards

No additional information available

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow. amber. Conforms to standard.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C (closed cup) ASTM D7094
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 1.07
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions. Not established.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### CAMEL #EU11062F

ATE CLP (oral)	569.541 mg/kg bodyweight
----------------	--------------------------

#### Benzyl benzoate (120-51-4)

LD50 oral rat	500 mg/kg (Source: NLM_CIP)
---------------	-----------------------------

LD50 oral	1160 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
--------------------	------------------------------

#### Ethyl vanillin (121-32-4)

LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
---------------	------------------------------

LD50 oral	3000 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
-----------------	---------------------------------

#### Methyl ester of rosin (partially hydrogenated) (8050-15-5)

LD50 oral rat	> 2000 mg/kg (Source: CHEMVIEW)
---------------	---------------------------------

LD50 dermal rabbit	> 10000 mg/kg (Source: ECHA_API)
--------------------	----------------------------------

#### Vanillin (121-33-5)

LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)
--------------------	----------------------------------

LD50 dermal	2600 mg/kg bodyweight
-------------	-----------------------

#### COUMARIN (91-64-5)

LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
---------------	----------------------------------

LD50 oral	290 mg/kg bodyweight
-----------	----------------------

LD50 dermal rat	293 mg/kg (Source: ECHA_API)
-----------------	------------------------------

#### Heliotropine (120-57-0)

LD50 oral rat	2700 mg/kg (Source: NLM_CIP)
---------------	------------------------------

LD50 oral	2700 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)
-----------------	---------------------------------

#### acetyl propionyl (600-14-6)

LD50 oral rat	3 g/kg (Source: NLM_CIP)
---------------	--------------------------

LD50 oral	3000 mg/kg bodyweight
-----------	-----------------------

LD50 dermal rabbit	> 2000 mg/kg (Source: NIOSH)
--------------------	------------------------------

LD50 dermal	2500 mg/kg bodyweight
-------------	-----------------------

#### 1,2-Cyclopentanedione, 3-methyl- (765-70-8)

LD50 oral	1067 mg/kg bodyweight
-----------	-----------------------

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

<b>Isobutyl acetate (110-19-0)</b>	
LD50 oral rat	15400 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	> 17400 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
<b>COUMARIN (91-64-5)</b>	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
<b>Isobutyl acetate (110-19-0)</b>	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
<b>acetyl propionyl (600-14-6)</b>	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
<b>Benzyl benzoate (120-51-4)</b>	
Viscosity, kinematic	7.456 mm <sup>2</sup> /s
<b>Heliotropine (120-57-0)</b>	
Viscosity, kinematic	Not applicable
<b>11.2. Information on other hazards</b>	
<b>11.2.1. Endocrine disrupting properties</b>	
No additional information available	
<b>11.2.2. Other information</b>	
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
<b>SECTION 12: Ecological information</b>	
<b>12.1. Toxicity</b>	
Ecology - general	: Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Toxic to aquatic life with long lasting effects.
<b>Benzyl benzoate (120-51-4)</b>	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
<b>Ethyl vanillin (121-32-4)</b>	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])

Heliotropine (120-57-0)	
LC50 - Fish [1]	2.5 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: ECHA)

Isobutyl acetate (110-19-0)	
LC50 - Fish [1]	17 mg/l (Exposure time: 96 h - Species: Oryzias latipes Source: ECHA)

### 12.2. Persistence and degradability

CAMEL #EU11062F	
Persistence and degradability	Not established.

Benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

CAMEL #EU11062F	
Bioaccumulative potential	Not established.

Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.

Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)

Methyl ester of rosin (partially hydrogenated) (8050-15-5)	
Partition coefficient n-octanol/water (Log Pow)	6.4 – 7.6 (at pH 6)

Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)

Heliotropine (120-57-0)	
Partition coefficient n-octanol/water (Log Pow)	1.2 (at 35 °C)

Isobutyl acetate (110-19-0)	
BCF - Fish [1]	(no significant bioconcentration)
Partition coefficient n-octanol/water (Log Pow)	2.3 (at 25 °C (at pH 7)

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.  
HP Code : HP3 - "Flammable:"  
– flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;  
– flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;  
– flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;  
– flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;  
– water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;  
– other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.  
HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure.  
HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
UN 3082	UN 3082	UN 3082	UN 3082	UN 3082
<b>14.2. UN proper shipping name</b>				
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate)
<b>Transport document description</b>				
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Benzyl Benzoate), 9, III
<b>14.3. Transport hazard class(es)</b>				
9	9	9	9	9

# CAMEL #EU11062F


## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
III	III	III	III	III
<b>14.5. Environmental hazards</b>				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	: 
Tunnel restriction code (ADR)	: -
EAC code	: •3Z

#### Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP1, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

#### Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Excepted quantities (ADN)	: E1
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP
Number of blue cones/lights (ADN)	: 0

### Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Excepted quantities (RID)	: E1
Packing instructions (RID)	: P001, IBC03, LP01, R001
Special packing provisions (RID)	: PP1
Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T4
Portable tank and bulk container special provisions (RID)	: TP1, TP29
Tank codes for RID tanks (RID)	: LGBV
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Special provisions for carriage - Loading, unloading and handling (RID)	: CW13, CW31
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 90

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	acetyl propionyl ; Isobutyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	CARAMEL #EU11062F ; Benzyl benzoate ; acetyl propionyl ; Isobutyl acetate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	CARAMEL #EU11062F ; Benzyl benzoate ; Methyl ester of rosin (partially hydrogenated)	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	acetyl propionyl ; Isobutyl acetate	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.



# CAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category	Threshold	Annex
Piperonal		120-57-0	2932 93 00	Category 1		Annex I

### 15.1.2. National regulations

#### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment  
SZW-lijst van kankerverwekkende stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed  
SZW-lijst van mutagene stoffen : Resin acids and Rosin acids, hydrogenated, methyl esters is listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed  
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product  
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Other information : None.

### Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

# CARAMEL #EU11062F

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.