

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 8/26/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : BLACK VANILLA OUD CLP #EU56468F

UFI : V2DN-DCJH-Q00A-S3FJ

Product code : EU56468F

Type of product : Perfumes, fragrances
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use

Industrial/Professional use spec : Industrial

For professional use only
: Perfumes, fragrances

Use of the substance/mixture : Perfumes, frag Function or use category : Odour agents

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE International GmbH

Mittlerer Weg 35 DE 79424 Auggen

Germany

T 49-7631-931-8900

SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number : 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731;

Brazil: +0-800-591-6042; India: +000-800-100-4086

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment – Chronic Hazard, H412

Category 3

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Harmful to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warning

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Contains : Hexyl cinnamic aldehyde; Benzyl salicylate; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-

tetramethyl-2-naphthalenyl)ethanone; Orange oil ; COUMARIN; Patchouli oil; Cyclamal;

Helional; Timberol; Eugenol

Hazard statements (CLP) : H317 - May cause an allergic skin reaction.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) : P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P321 - Specific treatment (see supplemental first aid instruction on this label).

Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(2-ethylhexyl) adipate substance with national workplace exposure limit(s) (PL)	CAS-No.: 103-23-1 EC-No.: 203-090-1 REACH-no: 01-2119439699-	29.1 – 58.245	Not classified
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040- 60	2 – 3.95	Eye Irrit. 2, H319
Ethylene brassylate	CAS-No.: 105-95-3 EC-No.: 203-347-8 REACH-no: 01-2119976314- 33	1.7 – 3.47	Aquatic Chronic 2, H411
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	0.9 – 1.78	Skin Sens. 1, H317 Aquatic Chronic 2, H411
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9 EC Index-No.: 607-754-00-5 REACH-no: 01-2119969442-	0.8 – 1.58	Eye Irrit. 2, H319 Skin Sens. 1B, H317 Aquatic Chronic 3, H412
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989- 04	0.8 – 1.57	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410

8/26/2024 (Issue date) EN (English) 2/24

Safety Data Sheet

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ethyl vanillin	CAS-No.: 121-32-4 EC-No.: 204-464-7 REACH-no: 01-211958961-24	0.6 – 1.28	Eye Irrit. 2, H319
Ethyl maltol	CAS-No.: 4940-11-8 EC-No.: 225-582-5	0.5 – 1	Acute Tox. 4 (Oral), H302
Orange oil	CAS-No.: 8008-57-9 EC-No.: 232-433-8 REACH-no: 01-2119493353- 35	0.3 – 0.67	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371- 33	0.2 – 0.4347	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756- 26	0.2 – 0.38	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Sandela	CAS-No.: 66068-84-6 EC-No.: 266-100-3	0.2 – 0.33	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Benzyl acetate substance with national workplace exposure limit(s) (BE, DK, ES, IE, LT, LV, PT, RO)	CAS-No.: 140-11-4 EC-No.: 205-399-7 REACH-no: 01-2119638272- 42	0.1 – 0.26	Aquatic Chronic 3, H412
Patchouli oil	CAS-No.: 8014-09-3 EC-No.: 616-944-7 EC Index-No.: 616-944-7	0.1 – 0.2	Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Cyclamal	CAS-No.: 103-95-7 EC-No.: 203-161-7 REACH-no: 01-2119970582- 32	0.1 – 0.14	Skin Irrit. 2, H315 Skin Sens. 1B, H317 Aquatic Chronic 2, H411
Helional	CAS-No.: 1205-17-0 EC-No.: 214-881-6 REACH-no: 01-2120740119- 58	0.1 – 0.14	Skin Sens. 1B, H317 Repr. 2, H361 Aquatic Chronic 2, H411
Timberol	CAS-No.: 70788-30-6 EC-No.: 274-892-7	0.1 – 0.1	Skin Sens. 1B, H317
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802- 33	0.1 – 0.1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
.betaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 127-91-3 EC-No.: 204-872-5	≤ 0.00225	Flam. Liq. 3, H226

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	≤ 0.00186	Not classified
.alphaPinene substance with national workplace exposure limit(s) (BE, EE, ES, LT, PT, SE, NO)	CAS-No.: 80-56-8 EC-No.: 201-291-9	≤ 0.00015	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Skin Sens. 1B, H317 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

persists. Rinse eyes with water as a precaution.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison

irst-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poisor center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire fighting water from entering the environment.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew

with proper protection. For further information refer to section 8: "Exposure

controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild

> soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.

Hygiene measures Contaminated work clothing should not be allowed out of the workplace. Wash

contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep away

from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep

container closed when not in use. Store in a well-ventilated place. Keep cool. Strong bases. Strong acids.

Incompatible materials Sources of ignition. Direct sunlight.

Storage temperature 25 °C

Storage area Store in a well-ventilated place. Store away from heat.

Special rules on packaging Store in a closed container. Packaging materials : Do not store in corrodable metal.

Germany

Incompatible products

Storage class (LGK, TRGS 510) : LGK 12 - Non-combustible liquids

8/26/2024 (Issue date) EN (English) 5/24

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Joint storage table LGK 2A LGK 2B LGK 3 LGK 4.1A LGK 1 LGK 4.1B LGK 4.2 LGK 4.3 LGK 5.1A LGK 5.1B LGK 6.1B LGK 5.1C LGK 5.2 LGK 6.1A LGK 6.1C LGK 6.1D

Joint storage not permitted for : LGK 1, LGK 6.2, LGK 7

Joint storage with restrictions permitted for : LGK 4.1A, LGK 4.3, LGK 5.1C

Joint storage permitted for : LGK 2A, LGK 2B, LGK 3, LGK 4.1B, LGK 4.2, LGK 5.1A, LGK 5.1B, LGK 5.2, LGK 6.1A,

LGK 6.1B, LGK 6.1C, LGK 6.1D, LGK 8A, LGK 8B, LGK 10, LGK 11, LGK 12, LGK 13, LGK

10-13

Switzerland

Storage class (LK) : LK 10/12 - Liquids

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Bis(2-ethylhexyl) adipate (103-23-1)		
Poland - Occupational Exposure Limits		
NDS (OEL TWA)	400 mg/m³	
Benzyl acetate (140-11-4)		
Belgium - Occupational Exposure Limits		
OEL TWA	62 mg/m³	
	10 ppm	
Denmark - Occupational Exposure Limits		
OEL TWA	61 mg/m³	
	10 ppm	
OEL STEL	122 mg/m³	
	20 ppm	
Ireland - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL STEL	30 ppm (calculated)	
Latvia - Occupational Exposure Limits		
OEL TWA	5 mg/m³	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	5 mg/m³	
Portugal - Occupational Exposure Limits		
OEL TWA	10 ppm	
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen	

Safety Data Sheet

Benzyl acetate (140-11-4)			
Romania - Occupational Exposure Limits	Romania - Occupational Exposure Limits		
OEL TWA	50 mg/m³		
	8 ppm		
OEL STEL	80 mg/m³		
	13 ppm		
Spain - Occupational Exposure Limits			
VLA-ED (OEL TWA)	62 mg/m³		
	10 ppm		
USA - ACGIH - Occupational Exposure Limits			
ACGIH OEL TWA	10 ppm		
ACGIH chemical category	Not Classifiable as a Human Carcinogen		
Dipropylene glycol monomethyl ether (34590-	94-8)		
EU - Indicative Occupational Exposure Limit (IOEL)			
IOEL TWA	308 mg/m³		
	50 ppm		
Remark	Possibility of significant uptake through the skin		
Austria - Occupational Exposure Limits			
MAK (OEL TWA)	307 mg/m³ (mixed isomers)		
	50 ppm (mixed isomers)		
MAK (OEL STEL)	614 mg/m³ (isomers mixtures)		
	100 ppm (isomers mixtures)		
OEL chemical category	Skin notation		
Belgium - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin, Skin notation		
Bulgaria - Occupational Exposure Limits			
OEL TWA	308 mg/m³		
	50 ppm		
Croatia - Occupational Exposure Limits			
GVI (OEL TWA)	308 mg/m³		
	50 ppm		
OEL chemical category	Skin notation		
Cyprus - Occupational Exposure Limits	Cyprus - Occupational Exposure Limits		
OEL TWA	308 mg/m³		
	50 ppm		
OEL chemical category	Skin-potential for cutaneous absorption		
Czech Republic - Occupational Exposure Limits			
PEL (OEL TWA)	270 mg/m³		

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
OEL chemical category	Potential for cutaneous absorption	
Denmark - Occupational Exposure Limits		
OEL TWA	309 mg/m³	
	50 ppm	
OEL STEL	618 mg/m³	
	100 ppm	
OEL chemical category	Potential for cutaneous absorption	
Estonia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Finland - Occupational Exposure Limits		
HTP (OEL TWA)	310 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
France - Occupational Exposure Limits		
VME (OEL TWA)	308 mg/m³ (restrictive limit)	
	50 ppm (restrictive limit)	
OEL chemical category	Risk of cutaneous absorption	
Germany - Occupational Exposure Limits (TRO	GS 900)	
AGW (OEL TWA)	310 mg/m³ (isomer mixture)	
	50 ppm (isomer mixture)	
Gibraltar - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL chemical category	Skin notation	
Greece - Occupational Exposure Limits		
OEL TWA	600 mg/m³	
	100 ppm	
OEL STEL	900 mg/m³	
	150 ppm	
OEL chemical category	skin - potential for cutaneous absorption	
Hungary - Occupational Exposure Limits		
AK (OEL TWA)	308 mg/m³	
Ireland - Occupational Exposure Limits		
OEL TWA	308 mg/m³ ((2-Methoxymethylethoxy)propanol)	
	50 ppm ((2-Methoxymethylethoxy)propanol)	
OEL STEL	924 mg/m³ (calculated (2-(2-Methoxypropoxy)-1-propanol)	
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)	

Safety Data Sheet

Potential for cutaneous absorption	Dipropylene glycol monomethyl ether (34590-94-8)		
OEL chemical category skin - potential for cutaneous absorption CEL themical category skin - potential for cutaneous absorption CEL TWA 50 ppm CEL themical category skin - potential for cutaneous exposure Lithuania - Occupational Exposure Limits OEL TWA) 308 mg/m² 50 ppm CEL chemical category skin - potential for cutaneous exposure Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol) CEL chemical category skin notation Luxembourg - Occupational Exposure Limits OEL TWA 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 50 ppm OEL chemical category Possibility of significant uptake through the skin Notherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 200 mg/m² (mixture of isomers: 1-(2-Methoxy)-t-methylethoxylpropan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-o	OEL chemical category	Potential for cutaneous absorption	
So ppm (1-(3-Methoxypropoxy)propan-1-ol)	Italy - Occupational Exposure Limits		
Skin - potential for cutaneous absorption	OEL TWA	308 mg/m³ (1-(3-Methoxypropoxy)propan-1-ol)	
Latvia - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category skin - potential for cutaneous exposure Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) 50 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category skin notation Litxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Matta - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Matta - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)pr		50 ppm (1-(3-Methoxypropoxy)propan-1-ol)	
OEL chemical category skin - potential for cutaneous exposure Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) 50 ppm (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 500 pm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Maita - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Maita - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits TGG-8u (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-met	OEL chemical category	skin - potential for cutaneous absorption	
Solyma S	Latvia - Occupational Exposure Limits		
OEL chemical category skin - potential for cutaneous exposure Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) FO ppm (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 450 mg/m² (2-(2-Methoxypropoxy)-propanol) TPRV (OEL STEL) 500 mg/m² (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Notherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (indicative limit value) OEL STEL 50 ppm (indicative limit value) OEL STEL 50 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 50 ppm	OEL TWA	308 mg/m³	
Lithuania - Occupational Exposure Limits IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) 50 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (indicative limit value) 50 ppm (indicative limit value) OEL STEL OEL TWA 308 mg/m² 50 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm		50 ppm	
IPRV (OEL TWA) 300 mg/m² (2-(2-Methoxypropoxy)-propanol) 50 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm OEL chemical category Possibility of significant uptake through the skin Method and a significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m² 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m² (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m² (indicative limit value) OEL TWA 308 mg/m² (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m² 50 ppm	OEL chemical category	skin - potential for cutaneous exposure	
So ppm (2-(2-Methoxypropoxy)-propanol)	Lithuania - Occupational Exposure Limits		
TPRV (OEL STEL) 450 mg/m³ (2-(2-Methoxypropoxy)-propanol) 75 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Metherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 509 ppm	IPRV (OEL TWA)	300 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
T5 ppm (2-(2-Methoxypropoxy)-propanol) OEL chemical category Skin notation		50 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL chemical category Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Matta - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Metherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	TPRV (OEL STEL)	450 mg/m³ (2-(2-Methoxypropoxy)-propanol)	
Luxembourg - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Maita - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm		75 ppm (2-(2-Methoxypropoxy)-propanol)	
OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL chemical category	Skin notation	
S0 ppm Possibility of significant uptake through the skin Malta - Occupational Exposure Limits	Luxembourg - Occupational Exposure Limits		
DEL chemical category Possibility of significant uptake through the skin Malta - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL TWA	308 mg/m³	
Malta - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 50 ppm Skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm		50 ppm	
OEL TWA 308 mg/m³ 50 ppm OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL chemical category	Possibility of significant uptake through the skin	
So pm	Malta - Occupational Exposure Limits		
OEL chemical category Possibility of significant uptake through the skin Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL TWA	308 mg/m³	
Netherlands - Occupational Exposure Limits TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm		50 ppm	
TGG-8u (OEL TWA) 300 mg/m³ 48.7 ppm Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL chemical category	Possibility of significant uptake through the skin	
Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL stel 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	Netherlands - Occupational Exposure Limits		
Poland - Occupational Exposure Limits NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	TGG-8u (OEL TWA)	300 mg/m³	
NDS (OEL TWA) 240 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL) 480 mg/m³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm		48.7 ppm	
2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol) NDSCh (OEL STEL)	Poland - Occupational Exposure Limits		
2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol) Portugal - Occupational Exposure Limits OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	NDS (OEL TWA)		
OEL TWA 308 mg/m³ (indicative limit value) 50 ppm (indicative limit value) OEL STEL 150 ppm OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	NDSCh (OEL STEL)		
DEL STEL DEL Chemical category Skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits DEL TWA 308 mg/m³ 50 ppm	Portugal - Occupational Exposure Limits		
OEL STEL OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL TWA	308 mg/m³ (indicative limit value)	
OEL chemical category skin - potential for cutaneous exposure indicative limit value Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm		50 ppm (indicative limit value)	
Romania - Occupational Exposure Limits OEL TWA 308 mg/m³ 50 ppm	OEL STEL	150 ppm	
OEL TWA 308 mg/m³ 50 ppm	OEL chemical category	skin - potential for cutaneous exposure indicative limit value	
50 ppm	Romania - Occupational Exposure Limits		
	OEL TWA	308 mg/m³	
OEL chemical category Skin notation		50 ppm	
	OEL chemical category	Skin notation	

Safety Data Sheet

Dipropylene glycol monomethyl ether (34590-94-8)		
Slovakia - Occupational Exposure Limits		
NPHV (OEL TWA)	308 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Slovenia - Occupational Exposure Limits		
OEL TWA	308 mg/m³	
	50 ppm	
OEL STEL	308 mg/m³	
	50 ppm	
OEL chemical category	Potential for cutaneous absorption	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	308 mg/m³ (indicative limit value)	
	50 ppm (indicative limit value)	
OEL chemical category	skin - potential for cutaneous absorption	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	300 mg/m³	
	50 ppm	
KGV (OEL STEL)	450 mg/m³	
	75 ppm	
OEL chemical category	Skin notation	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	308 mg/m³	
	50 ppm	
WEL STEL (OEL STEL)	924 mg/m³ (calculated)	
	150 ppm (calculated)	
WEL chemical category	Potential for cutaneous absorption	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	300 mg/m³	
	50 ppm	
Korttidsverdi (OEL STEL)	375 mg/m³ (value calculated)	
	75 ppm (value calculated)	
OEL chemical category	Skin notation	
Switzerland - Occupational Exposure Limits		
MAK (OEL TWA)	300 mg/m³ (aerosol, vapour)	
	50 ppm (aerosol, vapour)	
KZGW (OEL STEL)	300 mg/m³ (aerosol, vapour)	
	50 ppm (aerosol, vapour)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	50 ppm (Dipropylene glycol methyl ether)	

Safety Data Sheet

.alphaPinene (80-56-8)		
Belgium - Occupational Exposure Limits		
OEL TWA	20 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	150 mg/m³	
	25 ppm	
TPRV (OEL STEL)	300 mg/m³	
	50 ppm	
Portugal - Occupational Exposure Limits		
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	113 mg/m³	
	20 ppm	
OEL chemical category	Sensitizer	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
	25 ppm	
KGV (OEL STEL)	300 mg/m³	
	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	140 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
OEL chemical category	Skin notation	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	20 ppm (Turpentine and selected Monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

.betaPinene (127-91-3)		
Belgium - Occupational Exposure Limits		
OEL TWA	20 ppm	
Estonia - Occupational Exposure Limits		
OEL TWA	150 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
	25 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
OEL STEL	300 mg/m³ (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
	50 ppm (Turpentine produced from Nordic conifers has an irritating effect on the skin, monoterpenes, with the exception of 3-Carene, have a lesser effect)	
Lithuania - Occupational Exposure Limits		
IPRV (OEL TWA)	150 mg/m³	
	25 ppm	
TPRV (OEL STEL)	300 mg/m³	
	50 ppm	
Portugal - Occupational Exposure Limits		
OEL TWA	20 ppm (Turpentine and selected Monoterpenes)	
OEL chemical category	Sensitizer dermal, A4 - Not Classifiable as a Human Carcinogen	
Spain - Occupational Exposure Limits		
VLA-ED (OEL TWA)	113 mg/m³	
	20 ppm	
OEL chemical category	Sensitizer	
Sweden - Occupational Exposure Limits		
NGV (OEL TWA)	150 mg/m³	
	25 ppm	
KGV (OEL STEL)	300 mg/m³	
	50 ppm	
OEL chemical category	Sensitizer	
Norway - Occupational Exposure Limits		
Grenseverdi (OEL TWA)	140 mg/m³	
	25 ppm	
Korttidsverdi (OEL STEL)	175 mg/m³ (value calculated)	
	37.5 ppm (value calculated)	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA	20 ppm (Turpentine and selected Monoterpenes)	
ACGIH chemical category	Not Classifiable as a Human Carcinogen, dermal sensitizer	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):





8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear protective gloves.

8.2.2.3. Respiratory protection

Respiratory protection:

Wear appropriate mask

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Conforms to standard.

Odour characteristic. Odour threshold : Not available Melting point : Not applicable Freezing point : Not available Boiling point : Not available Flammability : Not applicable Lower explosion limit : Not available Upper explosion limit : Not available Flash point : > 93.3 °C

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature : Not available
Decomposition temperature : Not available
pH : Not available
Viscosity, kinematic : Not available
Solubility : Not available
Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : 0.004395473 mm Hg (calculated value)

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 22.736835 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Bis(2-ethylhexyl) adipate (103-23-1)	
LD50 oral rat	5600 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	8410 mg/kg (Source: NLM_CIP)
LC50 Inhalation - Rat	> 5.7 mg/l/4h
Vanillin (121-33-5)	
LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)

Safety Data Sheet

Vanillin (121-33-5)	
LD50 dermal	2600 mg/kg bodyweight
Ethylene brassylate (105-95-3)	
LD50 oral rat	> 5000 mg/kg (Source: ECHA)
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA)
Hexyl cinnamic aldehyde (101-86-0)	
LD50 oral rat	3100 mg/kg (Source: NLM_CIP)
LD50 oral	3100 mg/kg bodyweight
LD50 dermal rabbit	> 3000 mg/kg (Source: EPA_HPV)
LC50 Inhalation - Rat	> 5 mg/l/4h
Benzyl salicylate (118-58-1)	
LD50 oral rat	2227 mg/kg (Source: NLM_CIP)
LD50 oral	2200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
Ethyl vanillin (121-32-4)	
LD50 oral rat	1590 mg/kg (Source: NLM_CIP)
LD50 oral	3000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
Ethyl maltol (4940-11-8)	
LD50 oral rat	1150 mg/kg (Source: NLM_CIP)
LD50 oral	1200 mg/kg bodyweight
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)
Orange oil (8008-57-9)	
LD50 oral rat	4400 mg/kg (Source: NZ_CCID)
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)
benzyl benzoate (120-51-4)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	1160 mg/kg bodyweight
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)
COUMARIN (91-64-5)	
LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
Sandela (66068-84-6)	
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)
LC50 Inhalation - Rat	> 5.27 mg/l/4h
Benzyl acetate (140-11-4)	
LD50 oral rat	2490 mg/kg (Source: JAPAN_GHS)
LD50 oral	2490 mg/kg bodyweight

Safety Data Sheet

Benzyl acetate (140-11-4)		
LD50 dermal rabbit	> 5000 mg/kg (Source: JAPAN_GHS)	
Patchouli oil (8014-09-3)		
LD50 oral rat	> 5 g/kg (Source: NLM_CIP)	
Cyclamal (103-95-7)		
LD50 oral rat	3810 mg/kg (Source: NLM_CIP)	
LD50 oral	3810 mg/kg bodyweight	
LD50 dermal rat	> 5000 mg/kg (Source: ECHA_API)	
Helional (1205-17-0)		
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)	
Timberol (70788-30-6)		
LD50 dermal rabbit	> 2000 mg/kg (Source: ECHA_API)	
Eugenol (97-53-0)		
LD50 oral rat	1930 mg/kg (Source: NZ_CCID)	
LD50 oral	2500 mg/kg bodyweight	
Dipropylene glycol monomethyl ether (34590-	94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)	
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)	
.alphaPinene (80-56-8)		
LD50 oral rat	3700 mg/kg (Source: NLM_CIP)	
LD50 dermal rat	> 5000 mg/kg (Source: CHEMVIEW)	
.betaPinene (127-91-3)		
LD50 oral rat	> 5000 mg/kg (Source: EPA_HPV)	
LD50 dermal rabbit	> 5000 mg/kg (Source: CHEMVIEW)	
Skin corrosion/irritation : Serious eye damage/irritation :	Not classified Not classified	
Respiratory or skin sensitisation :	May cause an allergic skin reaction.	
Germ cell mutagenicity :	Not classified	
	Not classified	
Bis(2-ethylhexyl) adipate (103-23-1)		
IARC group	3 - Not classifiable	
COUMARIN (91-64-5)		
IARC group	3 - Not classifiable	
Benzyl acetate (140-11-4)		
IARC group	3 - Not classifiable	
Eugenol (97-53-0)		
IARC group	3 - Not classifiable	
Reproductive toxicity :	Not classified Not classified	
STOT-single exposure : STOT-repeated exposure :	Not classified Not classified	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aspiration hazard :	Not classified	
Orange oil (8008-57-9)		
Hydrocarbon	Yes	
benzyl benzoate (120-51-4)		
Viscosity, kinematic	7.456 mm²/s	
.alphaPinene (80-56-8)		
Hydrocarbon	Yes	
.betaPinene (127-91-3)		
Hydrocarbon	Yes	

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

: Harmful to aquatic life with long lasting effects. Ecology - general

Hazardous to the aquatic environment, short-term : Not classified

Hazardous to the aquatic environment, long-term

: Harmful to aquatic life with long lasting effects.

(chronic)

Bis(2-ethylhexyl) adipate (103-23-1)	
LC50 - Fish [1]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	0.48 – 0.85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: EPA)
EC50 - Crustacea [1]	> 1.6 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Benzyl salicylate (118-58-1)	
LC50 - Fish [1]	1.03 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Ethyl vanillin (121-32-4)	
LC50 - Fish [1]	81.4 – 94.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
Ethyl maltol (4940-11-8)	
LC50 - Fish [1]	> 85 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: ECHA)

Safety Data Sheet

benzyl benzoate (120-51-4)			
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)		
NOEC (chronic)	0.168 mg/l		
Eugenol (97-53-0)			
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)		
Dipropylene glycol monomethyl ether (34590-	94-8)		
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
.alphaPinene (80-56-8)			
LC50 - Fish [1]	0.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: IUCLID)		
EC50 - Crustacea [1]	41 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
12.2. Persistence and degradability			
BLACK VANILLA OUD CLP #EU56468F			
Persistence and degradability	Not established.		
Bis(2-ethylhexyl) adipate (103-23-1)			
Persistence and degradability	Rapidly degradable		
Vanillin (121-33-5)			
Persistence and degradability	Rapidly degradable		
Ethylene brassylate (105-95-3)			
Persistence and degradability	Rapidly degradable		
Hexyl cinnamic aldehyde (101-86-0)			
Persistence and degradability	Rapidly degradable		
Benzyl salicylate (118-58-1)			
Persistence and degradability	Rapidly degradable		
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethy	1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)		
Persistence and degradability	Rapidly degradable		
Ethyl vanillin (121-32-4)			
Persistence and degradability	Rapidly degradable		
Ethyl maltol (4940-11-8)			
Persistence and degradability	Rapidly degradable		
Orange oil (8008-57-9)			
Persistence and degradability	Rapidly degradable		
benzyl benzoate (120-51-4)			
Persistence and degradability	May cause long-term adverse effects in the environment.		
COUMARIN (91-64-5)			
Persistence and degradability	Rapidly degradable		

Safety Data Sheet

0	
Sandela (66068-84-6)	
Persistence and degradability	Rapidly degradable
Benzyl acetate (140-11-4)	
Persistence and degradability	Rapidly degradable
Patchouli oil (8014-09-3)	
Persistence and degradability	Rapidly degradable
Cyclamal (103-95-7)	
Persistence and degradability	Rapidly degradable
Helional (1205-17-0)	
Persistence and degradability	Rapidly degradable
Timberol (70788-30-6)	
Persistence and degradability	Rapidly degradable
Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-	94-8)
Persistence and degradability	Rapidly degradable
.alphaPinene (80-56-8)	
Persistence and degradability	Rapidly degradable
.betaPinene (127-91-3)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
BLACK VANILLA OUD CLP #EU56468F	
Bioaccumulative potential	Not established.
Bis(2-ethylhexyl) adipate (103-23-1)	
BCF - Fish [1]	(27 dimensionless)
Partition coefficient n-octanol/water (Log Pow)	8.94 (at 25 °C)
Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Ethylene brassylate (105-95-3)	
Partition coefficient n-octanol/water (Log Pow)	4.3 (at 25 °C (at pH 6.4-7)
Benzyl salicylate (118-58-1)	
Partition coefficient n-octanol/water (Log Pow)	4
Ethyl vanillin (121-32-4)	
Partition coefficient n-octanol/water (Log Pow)	1.61 (at 25 °C)
Ethyl maltol (4940-11-8)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 25 °C)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

honryl honroote (420 E4 4)		
benzyl benzoate (120-51-4)		
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)	
Bioaccumulative potential	Not established.	
Benzyl acetate (140-11-4)		
Partition coefficient n-octanol/water (Log Pow)	1.96 (at 25 °C (at pH 7)	
Cyclamal (103-95-7)		
Partition coefficient n-octanol/water (Log Pow)	3.4 (at 35 °C)	
Helional (1205-17-0)		
Partition coefficient n-octanol/water (Log Pow)	2.4 (at 25 °C)	
Timberol (70788-30-6)		
Partition coefficient n-octanol/water (Log Pow)	5.79 (at 25 °C (at pH 5.85)	
Eugenol (97-53-0)		
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5)	
Dipropylene glycol monomethyl ether (34590-94-8)		
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7)	
.alphaPinene (80-56-8)		
Partition coefficient n-octanol/water (Log Pow)	4.1	

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods

Product/Packaging disposal recommendations

Ecological information

HP Code

- : Dispose of contents/container in accordance with licensed collector's sorting instructions.
- : Dispose in a safe manner in accordance with local/national regulations.
- : Avoid release to the environment.
- : HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

8/26/2024 (Issue date) EN (English) 20/24

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID n	14.1. UN number or ID number			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping	14.2. UN proper shipping name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard o	14.3. Transport hazard class(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group	14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Orange oil ; .alpha Pinene ; .betaPinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	BLACK VANILLA OUD CLP #EU56468F; Hexyl cinnamic aldehyde; Benzyl salicylate; 1- (1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone; Orange oil; benzyl benzoate; Sandela; Patchouli oil; Cyclamal; Helional; Timberol; Eugenol; .alphaPinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	BLACK VANILLA OUD CLP #EU56468F; Ethylene brassylate; Hexyl cinnamic aldehyde; Benzyl salicylate; 1- (1,2,3,4,5,6,7,8- Octahydro-2,3,8,8- tetramethyl-2- naphthalenyl)ethanone; Orange oil; benzyl benzoate; Sandela; Benzyl acetate; Patchouli oil; Cyclamal; Helional; .alphaPinene	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
40.	Orange oil ; .alpha Pinene ; .betaPinene	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

VOC content : 22.736835 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Occupational diseases		
Code	Description	
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide	

Germany

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1). Water hazard class (WGK)

Hazardous Incident Ordinance (12. BlmSchV) Is not subject to the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category : A(2) - toxic for aquatic organisms, may have longterm hazardous effects in aquatic

: Orange oil ,Sandela,Timberol are listed

environment

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen : Orange oil ,Sandela,Timberol are listed SZW-lijst van reprotoxische stoffen - Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen -: None of the components are listed

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with

the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Other information · None

Full text of H- and EUH-statements:		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2	
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3	
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B

The classification complies with

: ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.